

# Crimp Information Sheet

Terminal Part Number: 15326268  
 Surface Plating: SN  
 Material Thickness [mm]: 0,30  
 Cross Section [mm<sup>2</sup>]: 0,35 | 0,50

*This document is non-contractual  
and for information only.*

*For more information, please  
consult your local sales office*



Cable Type codes: 1005  
 Crimp Process: (C) CRIMP ONLY - TERMINAL IS APPLIED CRIMP ONLY  
 Insulation Range  $\Phi$ [mm]: 1,45 - 1,88  
 Seal(s): 15366021

Cable type / seal	Arrangement	Nominal Insul. diam [mm]	Tear-out force [N]	CCH [mm]	Tol CCH [mm]	CCW [mm]	Tol CCW [mm]	ICH [mm]	Tol ICH [mm]	ICW [mm]	Tol ICW [mm]
1005 0,35 / 15366021		1,60	55	1,05	0,05	1,80	0,10	3,30	0,10	3,40	0,10
1005 0,50 / 15366021		1,74	80	1,10	0,05	1,80	0,10	3,50	0,10	3,40	0,10

Cable type code legend:

1005:

Industry Designator: SAE  
 Conductor Material: COPPER  
 Conductor Plating: NONE  
 Insul. Material: PVC, PVDF, XLPE  
 Insul. Wall Designator: THIN



# Crimp Information Sheet

Terminal Part Number: 15326268  
 Surface Plating: SN  
 Material Thickness [mm]: 0,30  
 Cross Section [mm<sup>2</sup>]: 0,50

*This document is non-contractual  
 and for information only.  
 For more information, please  
 consult your local sales office*

Cable Type codes: 1005  
 Crimp Process: (SR) SOLDER - REFLOW [LOW IMPEDANCE (SIR) CIRCUIT]  
 Insulation Range  $\Phi$ [mm]: 1,60 - 1,88  
 Seal(s): 15366021

Cable type / seal	Arrangement	Nominal Insul. diam [mm]	Tear-out force [N]	CCH [mm]	Tol CCH [mm]	CCW [mm]	Tol CCW [mm]	ICH [mm]	Tol ICH [mm]	ICW [mm]	Tol ICW [mm]
1005 0,50 / 15366021		1,74	80	1,10	0,05	1,80	0,10	3,50	0,10	3,40	0,10

## Cable type code legend:

1005:

Industry Designator: SAE  
 Conductor Material: COPPER  
 Conductor Plating: NONE  
 Insul. Material: PVC, PVDF, XLPE  
 Insul. Wall Designator: THIN



# Crimp Information Sheet

Terminal Part Number: 15326268  
 Surface Plating: SN  
 Material Thickness [mm]: 0,30  
 Cross Section [mm<sup>2</sup>]: 0,50

*This document is non-contractual  
 and for information only.  
 For more information, please  
 consult your local sales office*

Cable Type codes: 1007  
 Crimp Process: (C) CRIMP ONLY - TERMINAL IS APPLIED CRIMP ONLY  
 Insulation Range  $\Phi$ [mm]: 2,00 - 2,30  
 Seal(s): 15366060

Cable type / seal	Arrangement	Nominal Insul. diam [mm]	Tear-out force [N]	CCH [mm]	Tol CCH [mm]	CCW [mm]	Tol CCW [mm]	ICH [mm]	Tol ICH [mm]	ICW [mm]	Tol ICW [mm]
1007 0,50 / 15366060		2,15	80	1,10	0,05	1,80	0,10	3,50	0,10	3,40	0,10

## Cable type code legend:

1007:

Industry Designator: SAE  
 Conductor Material: COPPER  
 Conductor Plating: NONE  
 Insul. Material: PVC, XLPA/PVDF, XLPE  
 Insul. Wall Designator: REGULAR



# Crimp Information Sheet

Terminal Part Number: 15326268  
 Surface Plating: SN  
 Material Thickness [mm]: 0,30  
 Cross Section [mm<sup>2</sup>]: 0,50

*This document is non-contractual  
 and for information only.  
 For more information, please  
 consult your local sales office*

Cable Type codes: 1007  
 Crimp Process: (SR) SOLDER - REFLOW [LOW IMPEDANCE (SIR) CIRCUIT]  
 Insulation Range  $\Phi$ [mm]: 2,00 - 2,30  
 Seal(s): 15366060

Cable type / seal	Arrangement	Nominal Insul. diam [mm]	Tear-out force [N]	CCH [mm]	Tol CCH [mm]	CCW [mm]	Tol CCW [mm]	ICH [mm]	Tol ICH [mm]	ICW [mm]	Tol ICW [mm]
1007 0,50 / 15366060		2,15	80	1,10	0,05	1,80	0,10	3,50	0,10	3,40	0,10

## Cable type code legend:

1007:

Industry Designator: SAE  
 Conductor Material: COPPER  
 Conductor Plating: NONE  
 Insul. Material: PVC, XLPA/PVDF, XLPE  
 Insul. Wall Designator: REGULAR



# Crimp Information Sheet

Terminal Part Number: 15326268  
 Surface Plating: SN  
 Material Thickness [mm]: 0,30  
 Cross Section [mm<sup>2</sup>]: 0,35 | 0,50

*This document is non-contractual  
 and for information only.  
 For more information, please  
 consult your local sales office*

Cable Type codes: 1025  
 Crimp Process: (C) CRIMP ONLY - TERMINAL IS APPLIED CRIMP ONLY  
 Insulation Range  $\Phi$ [mm]: 1,47 - 1,85  
 Seal(s): 15366021

Cable type / seal	Arrangement	Nominal Insul. diam [mm]	Tear-out force [N]	CCH [mm]	Tol CCH [mm]	CCW [mm]	Tol CCW [mm]	ICH [mm]	Tol ICH [mm]	ICW [mm]	Tol ICW [mm]
1025 0,35 / 15366021		1,55	55	1,05	0,05	1,80	0,10	3,30	0,10	3,40	0,10
1025 0,50 / 15366021		1,73	80	1,10	0,05	1,80	0,10	3,50	0,10	3,40	0,10

Cable type code legend:

1025:

Industry Designator: SAE  
 Conductor Material: COPPER  
 Conductor Plating: SN  
 Insul. Material: FLUORPOLYM, HDPE, PBT, PE, PVC, XLPE  
 Insul. Wall Designator: THIN



# Crimp Information Sheet

Terminal Part Number: 15326268  
 Surface Plating: SN  
 Material Thickness [mm]: 0,30  
 Cross Section [mm<sup>2</sup>]: 0,50

*This document is non-contractual  
 and for information only.  
 For more information, please  
 consult your local sales office*

Cable Type codes: 1026  
 Crimp Process: (C) CRIMP ONLY - TERMINAL IS APPLIED CRIMP ONLY  
 Insulation Range  $\Phi$ [mm]: 2,00 - 2,30  
 Seal(s): 15366060

Cable type / seal	Arrangement	Nominal Insul. diam [mm]	Tear-out force [N]	CCH [mm]	Tol CCH [mm]	CCW [mm]	Tol CCW [mm]	ICH [mm]	Tol ICH [mm]	ICW [mm]	Tol ICW [mm]
1026 0,50 / 15366060		2,15	80	1,10	0,05	1,80	0,10	3,50	0,10	3,40	0,10

## Cable type code legend:

1026:

Industry Designator: SAE  
 Conductor Material: COPPER  
 Conductor Plating: SN  
 Insul. Material: HDPE, PVC, XLPE  
 Insul. Wall Designator: REGULAR



# Crimp Information Sheet

Terminal Part Number: 15326268  
 Surface Plating: SN  
 Material Thickness [mm]: 0,30  
 Cross Section [mm<sup>2</sup>]: 0,50

*This document is non-contractual  
 and for information only.  
 For more information, please  
 consult your local sales office*

Cable Type codes: 1035  
 Crimp Process: (C) CRIMP ONLY - TERMINAL IS APPLIED CRIMP ONLY  
 Insulation Range  $\Phi$ [mm]: 2,00 - 2,30  
 Seal(s): 15366060

Cable type / seal	Arrangement	Nominal Insul. diam [mm]	Tear-out force [N]	CCH [mm]	Tol CCH [mm]	CCW [mm]	Tol CCW [mm]	ICH [mm]	Tol ICH [mm]	ICW [mm]	Tol ICW [mm]
1035 0,50 / 15366060		2,15	80	1,10	0,05	1,80	0,10	3,50	0,10	3,40	0,10

## Cable type code legend:

1035:

Industry Designator: SAE  
 Conductor Material: COPPER  
 Conductor Plating: NONE  
 Insul. Material: XLPE  
 Insul. Wall Designator: REGULAR



# Crimp Information Sheet

Terminal Part Number: 15326268  
 Surface Plating: SN  
 Material Thickness [mm]: 0,30  
 Cross Section [mm<sup>2</sup>]: 0,35

*This document is non-contractual  
 and for information only.  
 For more information, please  
 consult your local sales office*

Cable Type codes: 1047  
 Crimp Process: (C) CRIMP ONLY - TERMINAL IS APPLIED CRIMP ONLY  
 Insulation Range  $\Phi$ [mm]: 1,40 - 1,75  
 Seal(s): 15366021

Cable type / seal	Arrangement	Nominal Insul. diam [mm]	Tear-out force [N]	CCH [mm]	Tol CCH [mm]	CCW [mm]	Tol CCW [mm]	ICH [mm]	Tol ICH [mm]	ICW [mm]	Tol ICW [mm]
1047 0,35 / 15366021		1,58	70	1,05	0,05	1,80	0,10	3,30	0,10	3,40	0,10

## Cable type code legend:

1047:

Industry Designator: SAE  
 Conductor Material: COPPER  
 Conductor Plating: NONE  
 Insul. Material: PVC, XLPE  
 Insul. Wall Designator: THIN





# Crimp Information Sheet

Terminal Part Number: 15326268  
 Surface Plating: SN  
 Material Thickness [mm]: 0,30  
 Cross Section [mm<sup>2</sup>]: 0,35

*This document is non-contractual  
 and for information only.  
 For more information, please  
 consult your local sales office*

Cable Type codes: 1055  
 Crimp Process: (C) CRIMP ONLY - TERMINAL IS APPLIED CRIMP ONLY  
 Insulation Range  $\Phi$ [mm]: 1,45 - 1,75  
 Seal(s): 15366021

Cable type / seal	Arrangement	Nominal Insul. diam [mm]	Tear-out force [N]	CCH [mm]	Tol CCH [mm]	CCW [mm]	Tol CCW [mm]	ICH [mm]	Tol ICH [mm]	ICW [mm]	Tol ICW [mm]
1055 0,35 / 15366021		1,60	70	1,05	0,05	1,80	0,10	3,30	0,10	3,40	0,10

## Cable type code legend:

1055:

Industry Designator: SAE  
 Conductor Material: COPPER  
 Conductor Plating: SN  
 Insul. Material: HDPE, PVC, XLPE  
 Insul. Wall Designator: THIN



# Crimp Information Sheet

Terminal Part Number: 15326268  
 Surface Plating: SN  
 Material Thickness [mm]: 0,30  
 Cross Section [mm<sup>2</sup>]: 0,50

*This document is non-contractual  
 and for information only.  
 For more information, please  
 consult your local sales office*

Cable Type codes: 1092  
 Crimp Process: (C) CRIMP ONLY - TERMINAL IS APPLIED CRIMP ONLY  
 Insulation Range  $\Phi$ [mm]: 2,00 - 2,30  
 Seal(s): 15366060

Cable type / seal	Arrangement	Nominal Insul. diam [mm]	Tear-out force [N]	CCH [mm]	Tol CCH [mm]	CCW [mm]	Tol CCW [mm]	ICH [mm]	Tol ICH [mm]	ICW [mm]	Tol ICW [mm]
1092 0,50 / 15366060		2,15	80	1,10	0,05	1,80	0,10	3,50	0,10	3,40	0,10

## Cable type code legend:

1092:

Industry Designator: SAE  
 Conductor Material: ALLOY  
 Conductor Plating: NONE  
 Insul. Material: XLPE  
 Insul. Wall Designator: REGULAR



# Crimp Information Sheet

Terminal Part Number: 15326268  
 Surface Plating: SN  
 Material Thickness [mm]: 0,30  
 Cross Section [mm<sup>2</sup>]: 0,50

*This document is non-contractual  
 and for information only.*

*For more information, please  
 consult your local sales office*



Cable Type codes: 2006  
 Crimp Process: (C) CRIMP ONLY - TERMINAL IS APPLIED CRIMP ONLY  
 Insulation Range  $\Phi$ [mm]: 2,00 - 2,35  
 Seal(s): 15366060

Cable type / seal	Arrangement	Nominal Insul. diam [mm]	Tear-out force [N]	CCH [mm]	Tol CCH [mm]	CCW [mm]	Tol CCW [mm]	ICH [mm]	Tol ICH [mm]	ICW [mm]	Tol ICW [mm]
2006 0,50 / 15366060		2,18	80	1,10	0,05	1,80	0,10	3,50	0,10	3,40	0,10

## Cable type code legend:

2006:

Industry Designator: ISO  
 Conductor Material: COPPER  
 Conductor Plating: NONE  
 Insul. Material: EPR, PVC, XLPE  
 Insul. Wall Designator: REGULAR



# Crimp Information Sheet

Terminal Part Number: 15326268  
 Surface Plating: SN  
 Material Thickness [mm]: 0,30  
 Cross Section [mm<sup>2</sup>]: 0,35 | 0,50

*This document is non-contractual  
 and for information only.  
 For more information, please  
 consult your local sales office*

Cable Type codes: 2010  
 Crimp Process: (C) CRIMP ONLY - TERMINAL IS APPLIED CRIMP ONLY  
 Insulation Range  $\Phi$ [mm]: 1,20 - 1,70  
 Seal(s): 12191226 | 15366021

Cable type / seal	Arrangement	Nominal Insul. diam [mm]	Tear-out force [N]	CCH [mm]	Tol CCH [mm]	CCW [mm]	Tol CCW [mm]	ICH [mm]	Tol ICH [mm]	ICW [mm]	Tol ICW [mm]
2010 0,35 / 12191226		1,34	50	1,15	0,05	1,65	0,10	3,30	0,10	3,50	0,10
2010 0,35 / 15366021		1,34	50	1,15	0,05	1,65	0,10	3,30	0,10	3,50	0,10
2010 0,50 / 12191226		1,50	80	1,25	0,05	1,70	0,10	3,40	0,10	3,50	0,10
2010 0,50 / 15366021		1,50	80	1,25	0,05	1,70	0,10	3,40	0,10	3,50	0,10

## Cable type code legend:

2010: ACW0219, FIAT T2 FLRY, FL RENAULT R1, FL RENAULT R3, FLR (AGP0219), FLR2X-A, FLR4Y-A, FLR9Y, FLRX-B, FLRY-A, FLRYB, FLRY-B



Industry Designator: DIN

Conductor Material: COPPER

Conductor Plating: NONE

Insul. Material: PA, POLYOLEFIN, PP, PVC, SYNTHRESIN, XLCOPOLY, XLPBT, XLPE, XLPE/PVDF, XLPVC

Insul. Wall Designator: THIN



# Crimp Information Sheet

Terminal Part Number: 15326268  
 Surface Plating: SN  
 Material Thickness [mm]: 0,30  
 Cross Section [mm<sup>2</sup>]: 0,50


*This document is non-contractual  
 and for information only.  
 For more information, please  
 consult your local sales office*

Cable Type codes: 2011  
 Crimp Process: (C) CRIMP ONLY - TERMINAL IS APPLIED CRIMP ONLY  
 Insulation Range  $\Phi$ [mm]: 2,00 - 2,30  
 Seal(s): 15366021 | 15366060

Cable type / seal	Arrangement	Nominal Insul. diam [mm]	Tear-out force [N]	CCH [mm]	Tol CCH [mm]	CCW [mm]	Tol CCW [mm]	ICH [mm]	Tol ICH [mm]	ICW [mm]	Tol ICW [mm]
2011 0,50 / 15366021		2,15	75	1,10	0,05	1,80	0,10	3,50	0,10	3,50	0,10
2011 0,50 / 15366060		2,15	80	1,10	0,05	1,80	0,10	3,50	0,10	3,40	0,10

## Cable type code legend:

2011: FL33X, FLK, FLY, FLYKW, IH WIRE  
 Industry Designator: DIN  
 Conductor Material: COPPER  
 Conductor Plating: NONE  
 Insul. Material: P/EST, PE, PVC, XLPE  
 Insul. Wall Designator: REGULAR



# Crimp Information Sheet

Terminal Part Number: 15326268  
 Surface Plating: SN  
 Material Thickness [mm]: 0,30  
 Cross Section [mm<sup>2</sup>]: 0,35



*This document is non-contractual  
 and for information only.  
 For more information, please  
 consult your local sales office*

Cable Type codes: 2016  
 Crimp Process: (C) CRIMP ONLY - TERMINAL IS APPLIED CRIMP ONLY  
 Insulation Range  $\Phi$ [mm]: 0,62 - 0,67  
 Seal(s): 15366021

Cable type / seal	Arrangement	Nominal Insul. diam [mm]	Tear-out force [N]	CCH [mm]	Tol CCH [mm]	CCW [mm]	Tol CCW [mm]	ICH [mm]	Tol ICH [mm]	ICW [mm]	Tol ICW [mm]
2016 0,35 / 15366021		0,65	50	1,05	0,05	1,90	0,10	3,15	0,10	3,70	0,10

## Cable type code legend:

2016: DIN-CORE  
 Industry Designator: DIN  
 Conductor Material: COPPER  
 Conductor Plating: SN  
 Insul. Material: NONE  
 Insul. Wall Designator: NONE



# Crimp Information Sheet

Terminal Part Number: 15326268  
 Surface Plating: SN  
 Material Thickness [mm]: 0,30  
 Cross Section [mm<sup>2</sup>]: 0,35 | 0,50



*This document is non-contractual  
 and for information only.  
 For more information, please  
 consult your local sales office*

Cable Type codes: 2017  
 Crimp Process: (C) CRIMP ONLY - TERMINAL IS APPLIED CRIMP ONLY  
 Insulation Range  $\Phi$ [mm]: 1,10 - 1,70  
 Seal(s): 15366021 | 12191152

Cable type / seal	Arrangement	Nominal Insul. diam [mm]	Tear-out force [N]	CCH [mm]	Tol CCH [mm]	CCW [mm]	Tol CCW [mm]	ICH [mm]	Tol ICH [mm]	ICW [mm]	Tol ICW [mm]
2017 0,35 / 15366021		1,25	50	1,15	0,05	1,65	0,10	2,90	0,10	3,50	0,10
2017 0,50 / 15366021		1,50	80	1,25	0,05	1,70	0,10	3,10	0,10	3,50	0,10
2017 0,50 / 12191152		1,50	80	1,25	0,05	1,70	0,10	3,10	0,10	3,50	0,10

## Cable type code legend:

2017: FLR41X-B, FLRY-A  
 Industry Designator: DIN  
 Conductor Material: COPPER  
 Conductor Plating: SN  
 Insul. Material: PA, PP, PVC, XLPE  
 Insul. Wall Designator: THIN



# Crimp Information Sheet

Terminal Part Number: 15326268  
 Surface Plating: SN  
 Material Thickness [mm]: 0,30  
 Cross Section [mm<sup>2</sup>]: 0,50



*This document is non-contractual  
 and for information only.  
 For more information, please  
 consult your local sales office*

Cable Type codes: 2021  
 Crimp Process: (C) CRIMP ONLY - TERMINAL IS APPLIED CRIMP ONLY  
 Insulation Range  $\Phi$ [mm]: 1,20 - 1,70  
 Seal(s): 15366021

Cable type / seal	Arrangement	Nominal Insul. diam [mm]	Tear-out force [N]	CCH [mm]	Tol CCH [mm]	CCW [mm]	Tol CCW [mm]	ICH [mm]	Tol ICH [mm]	ICW [mm]	Tol ICW [mm]
2021 0,50 / 15366021		1,45	80	1,10	0,05	1,80	0,10	3,50	0,10	3,40	0,10

## Cable type code legend:

2021: FLR6Y-A, FLR6Y-B  
 Industry Designator: DIN  
 Conductor Material: COPPER  
 Conductor Plating: NONE  
 Insul. Material: ETFE, FEP, XLETFE  
 Insul. Wall Designator: THIN





# Crimp Information Sheet

Terminal Part Number: 15326268  
 Surface Plating: SN  
 Material Thickness [mm]: 0,30  
 Cross Section [mm<sup>2</sup>]: 0,50



*This document is non-contractual  
 and for information only.  
 For more information, please  
 consult your local sales office*

Cable Type codes: 2021  
 Crimp Process: (R) SOLDER - REFLOW [NON-SIR CIRCUIT] CORE IS DIP SOLD  
 Insulation Range  $\Phi$ [mm]: 1,20 - 1,70  
 Seal(s): 15366021

Cable type / seal	Arrangement	Nominal Insul. diam [mm]	Tear-out force [N]	CCH [mm]	Tol CCH [mm]	CCW [mm]	Tol CCW [mm]	ICH [mm]	Tol ICH [mm]	ICW [mm]	Tol ICW [mm]
2021 0,50 / 15366021		1,45	80	1,10	0,05	1,80	0,10	3,50	0,10	3,40	0,10

## Cable type code legend:

2021: FLR6Y-A, FLR6Y-B  
 Industry Designator: DIN  
 Conductor Material: COPPER  
 Conductor Plating: NONE  
 Insul. Material: ETFE, FEP, XLETFE  
 Insul. Wall Designator: THIN



# Crimp Information Sheet

Terminal Part Number: 15326268  
 Surface Plating: SN  
 Material Thickness [mm]: 0,30  
 Cross Section [mm<sup>2</sup>]: 0,35

*This document is non-contractual  
 and for information only.*

*For more information, please  
 consult your local sales office*



Cable Type codes: 2041  
 Crimp Process: (C) CRIMP ONLY - TERMINAL IS APPLIED CRIMP ONLY  
 Insulation Range  $\Phi$ [mm]: 1,23 - 1,40  
 Seal(s): 15366021

Cable type / seal	Arrangement	Nominal Insul. diam [mm]	Tear-out force [N]	CCH [mm]	Tol CCH [mm]	CCW [mm]	Tol CCW [mm]	ICH [mm]	Tol ICH [mm]	ICW [mm]	Tol ICW [mm]
2041 0,35 / 15366021		1,32	50	1,10	0,05	1,80	0,10	2,60	0,10	3,50	0,10

## Cable type code legend:

2041:

Industry Designator: ISO  
 Conductor Material: COPPER  
 Conductor Plating: NONE  
 Insul. Material: PPE  
 Insul. Wall Designator: THIN



# Crimp Information Sheet

Terminal Part Number: 15326268  
 Surface Plating: SN  
 Material Thickness [mm]: 0,30  
 Cross Section [mm<sup>2</sup>]: 0,35 | 0,50



*This document is non-contractual  
 and for information only.  
 For more information, please  
 consult your local sales office*

Cable Type codes: 2053  
 Crimp Process: (C) CRIMP ONLY - TERMINAL IS APPLIED CRIMP ONLY  
 Insulation Range  $\Phi$ [mm]: 1,20 - 1,60  
 Seal(s): 12191226

Cable type / seal	Arrangement	Nominal Insul. diam [mm]	Tear-out force [N]	CCH [mm]	Tol CCH [mm]	CCW [mm]	Tol CCW [mm]	ICH [mm]	Tol ICH [mm]	ICW [mm]	Tol ICW [mm]
2053 0,35 / 12191226		1,30	50	1,15	0,05	1,70	0,10	2,80	0,10	3,60	0,10
2053 0,50 / 12191226		1,50	80	1,25	0,05	1,70	0,10	2,90	0,10	3,60	0,10

## Cable type code legend:

2053: PSA T2 ZH ID, PSA T3 ZH ID, PSA T4 ZH ID  
 Industry Designator: PSA  
 Conductor Material: COPPER  
 Conductor Plating: NONE  
 Insul. Material: POLYOLEFIN, X-POLY  
 Insul. Wall Designator: ID



# Crimp Information Sheet

Terminal Part Number: 15326268  
 Surface Plating: SN  
 Material Thickness [mm]: 0,30  
 Cross Section [mm<sup>2</sup>]: 0,35 | 0,50


*This document is non-contractual  
 and for information only.  
 For more information, please  
 consult your local sales office*

Cable Type codes: 2054  
 Crimp Process: (C) CRIMP ONLY - TERMINAL IS APPLIED CRIMP ONLY  
 Insulation Range  $\Phi$ [mm]: 1,25 - 1,70  
 Seal(s): 12191226 | 15366021

Cable type / seal	Arrangement	Nominal Insul. diam [mm]	Tear-out force [N]	CCH [mm]	Tol CCH [mm]	CCW [mm]	Tol CCW [mm]	ICH [mm]	Tol ICH [mm]	ICW [mm]	Tol ICW [mm]
2054 0,35 / 12191226		1,33	50	1,15	0,05	1,70	0,10	2,90	0,10	3,50	0,10
2054 0,50 / 15366021		1,55	80	1,15	0,05	1,70	0,10	3,30	0,10	3,60	0,10
2054 0,50 / 12191226		1,55	80	1,25	0,05	1,70	0,10	3,10	0,10	3,50	0,10

## Cable type code legend:

2054: PSA T2 IR, PSA T3 IR, PSA T3 ZH IR, PSA T4 LH IR  
 Industry Designator: PSA  
 Conductor Material: COPPER  
 Conductor Plating: NONE  
 Insul. Material: POLYOLEFIN, PVC, X-POLY  
 Insul. Wall Designator: IR



# Crimp Information Sheet

Terminal Part Number: 15326268  
 Surface Plating: SN  
 Material Thickness [mm]: 0,30  
 Cross Section [mm<sup>2</sup>]: 0,35

*This document is non-contractual  
 and for information only.  
 For more information, please  
 consult your local sales office*

Cable Type codes: 2083  
 Crimp Process: (C) CRIMP ONLY - TERMINAL IS APPLIED CRIMP ONLY  
 Insulation Range  $\Phi$ [mm]: 1,20 - 1,40  
 Seal(s): 15366021

Cable type / seal	Arrangement	Nominal Insul. diam [mm]	Tear-out force [N]	CCH [mm]	Tol CCH [mm]	CCW [mm]	Tol CCW [mm]	ICH [mm]	Tol ICH [mm]	ICW [mm]	Tol ICW [mm]
2083 0,35 / 15366021		1,30	55	1,05	0,05	1,80	0,10	2,90	0,10	3,40	0,10

## Cable type code legend:

2083:

Industry Designator: ISO  
 Conductor Material: COPPER  
 Conductor Plating: NONE  
 Insul. Material: PVC (YW)  
 Insul. Wall Designator: THIN



# Crimp Information Sheet

Terminal Part Number: 15326268  
 Surface Plating: SN  
 Material Thickness [mm]: 0,30  
 Cross Section [mm<sup>2</sup>]: 0,30 | 0,50



*This document is non-contractual  
 and for information only.  
 For more information, please  
 consult your local sales office*

Cable Type codes: 3004  
 Crimp Process: (C) CRIMP ONLY - TERMINAL IS APPLIED CRIMP ONLY  
 Insulation Range  $\Phi$ [mm]: 1,30 - 1,70  
 Seal(s): 15366021

Cable type / seal	Arrangement	Nominal Insul. diam [mm]	Tear-out force [N]	CCH [mm]	Tol CCH [mm]	CCW [mm]	Tol CCW [mm]	ICH [mm]	Tol ICH [mm]	ICW [mm]	Tol ICW [mm]
3004 0,30 / 15366021		1,40	50	1,05	0,05	1,75	0,10	3,20	0,10	3,50	0,10
3004 0,50 / 15366021		1,60	88	1,10	0,05	1,75	0,10	3,30	0,10	3,50	0,10

## Cable type code legend:

3004: AVSS  
 Industry Designator: JIS/JA  
 Conductor Material: COPPER  
 Conductor Plating: NONE  
 Insul. Material: PVC, XLPE, X-PVC  
 Insul. Wall Designator: THIN



# Crimp Information Sheet

Terminal Part Number: 15326268  
 Surface Plating: SN  
 Material Thickness [mm]: 0,30  
 Cross Section [mm<sup>2</sup>]: 0,50

*This document is non-contractual  
 and for information only.  
 For more information, please  
 consult your local sales office*

Cable Type codes: 8000  
 Crimp Process: (C) CRIMP ONLY - TERMINAL IS APPLIED CRIMP ONLY  
 Insulation Range  $\Phi$ [mm]: 1,40 - 1,60  
 Seal(s): 15366021

Cable type / seal	Arrangement	Nominal Insul. diam [mm]	Tear-out force [N]	CCH [mm]	Tol CCH [mm]	CCW [mm]	Tol CCW [mm]	ICH [mm]	Tol ICH [mm]	ICW [mm]	Tol ICW [mm]
8000 0,50 / 15366021		1,50	80	1,10	0,05	1,80	0,10	3,50	0,10	3,40	0,10

## Cable type code legend:

8000:

Industry Designator: N/G  
 Conductor Material: COPPER  
 Conductor Plating: NONE  
 Insul. Material: SYNTHRESIN  
 Insul. Wall Designator: THIN



# Crimp Information Sheet

Terminal Part Number: 15326268  
 Surface Plating: SN  
 Material Thickness [mm]: 0,30  
 Cross Section [mm<sup>2</sup>]: 0,50

*This document is non-contractual  
 and for information only.  
 For more information, please  
 consult your local sales office*

Cable Type codes: 9000  
 Crimp Process: (C) CRIMP ONLY - TERMINAL IS APPLIED CRIMP ONLY  
 Insulation Range  $\Phi$ [mm]: 1,90 - 2,05  
 Seal(s): 15366060

Cable type / seal	Arrangement	Nominal Insul. diam [mm]	Tear-out force [N]	CCH [mm]	Tol CCH [mm]	CCW [mm]	Tol CCW [mm]	ICH [mm]	Tol ICH [mm]	ICW [mm]	Tol ICW [mm]
9000 0,50 / 15366060		1,98	80	1,10	0,05	1,80	0,10	3,50	0,10	3,40	0,10

## Cable type code legend:

9000:

Industry Designator: MISC  
 Conductor Material: COPPER  
 Conductor Plating: NONE  
 Insul. Material: PVDF  
 Insul. Wall Designator: MIX





# Crimp Information Sheet

Terminal Part Number: 15326268  
 Surface Plating: SN  
 Material Thickness [mm]: 0,30  
 Cross Section [mm<sup>2</sup>]: 0,50

*This document is non-contractual  
 and for information only.  
 For more information, please  
 consult your local sales office*

Cable Type codes: 9003  
 Crimp Process: (C) CRIMP ONLY - TERMINAL IS APPLIED CRIMP ONLY  
 Insulation Range  $\Phi$ [mm]: 1,92 - 2,06  
 Seal(s): 15366060

Cable type / seal	Arrangement	Nominal Insul. diam [mm]	Tear-out force [N]	CCH [mm]	Tol CCH [mm]	CCW [mm]	Tol CCW [mm]	ICH [mm]	Tol ICH [mm]	ICW [mm]	Tol ICW [mm]
9003 0,50 / 15366060		1,99	80	1,10	0,05	1,80	0,10	3,50	0,10	3,40	0,10

## Cable type code legend:

9003:

Industry Designator: N/G  
 Conductor Material: COPPER  
 Conductor Plating: SN  
 Insul. Material: PVDF  
 Insul. Wall Designator: MIX

