
# 118(PA) CONNECTOR



### WITH LANCE HOUSING LOCKING TERMINAL

- ▶Specially designed for circuits in low voltage applications. These connectors are suitable for miniaturization, high density and reliability.
- ▶ Easy insertion and extraction permit easy matching and unmatching of connector assemblies.
- ▶These connectors consist of Plug Housing and Receptacle Housing for multiple-pole connection.
- ▶Designed to prevent false-connection and to maintain stable connection under vibration and extreme environmental conditions.

#### **○** TERMINAL




Part No.	Wire Range		Tab	Material		Dimension(mm)			Τψρε
r die 140.	AWG	mm²	Thick.	Thick.	finish	L	€	W	Τήρο
ST730383-3	24-20	AVSS 0.2~0.5	0.64	0.4	Brass Pre-Tin	17.6	5.6	4.1	
ST730186-3	18-14	AVSS 0.85~2.27	0.64	0.4	Brass Pre-Tin	17.6	5.6	4.1	A
ST730192-3	14-13	AVSS 2.0 AVSS 2.5	0.64	0.4	Brass Pre-Tin	17.6	5.6	4.1	
ST740393-3	24-20	AVSS 0.2~0.5	0.64	0.3	Brass Pre-Tin	28.0	15.0	3.0	
ST740315-3	20-18	AVSS 0.5~0.85	0.64	0.3	Brass Pre-Tin	28.0	15.0	3.0	(D)
ST740187-3	18-14	AVSS 0.85~2.27	0.64	0.3	Brass Pre-Tin	28.0	15.0	3.0	B
ST740193-3	14-13	AVSS 2.0 AVS 2.5	0.64	0.3	Brass Pre-Tin	28.0	15.0	3.0	

### **BS** CONNECTOR

# BS CLIPHOUSING THE CLIPIS MOUNTED ON FEMALE HOUSING ONLY.

- ▶ Pre-sealed connectors are ideal for waterproof automotive circuit applications.
- ▶BS connectors for 3mm receptacle and tab terminals are easy to handle and water-proof
- ▶ Specially designed O-Ring in the receptacle housing.
- ▶Wire seal material is silicone rubber. The housings are compounded with PBT-GLASS, and are waterproof.
- ▶ These two parts, male and female connectors couple with minimal assembly force. The built-in locking device assures firm water and dust proof connection.

#### **O** HOUSING





### **BS** CONNECTOR

### **O** HOUSING

Poles	Receptacle housi	ng for female terminal	Plug housing for male terminal	Wire Seal
	MG640174	MG640195	MG610173	MG680175
6	43.0	43.0	Ø23.6 44.5	7.0
	MG 640196		MG610176	MG 680178
9	42.6	Ø30.4	Ø27.3 43.5	Ø27.5 7.0
12	MG 640197		MG610179	MG680181
	42.6	Ø32.5	Ø29.5 43.5	Ø30.1 7.0

Suitable Terminal: ST730383, ST731086, ST730192, ST740393, ST740315, ST740187, ST740193

### CLIP

