


NOTES

- UNLESS OTHERWISE SPECIFIED AND/OR INDICATED: DIMENSIONS ARE TO FACE OF VIEW SHOWN AND AUTOMATICALLY ROUNDED BY COMPUTER FOR INSPECTION (SEE MATH MODEL FOR PRECISE DIMENSIONS). FOR ALL OTHER DIMENSIONS NOT SHOWN BUT REQUIRED FOR TOOL BUILD, SEE MATH MODEL FOR PRECISE TOOL PATH DATA. ALL RADII 0.5. DRAFT IS 0° 30' MAX ON ALL OUTSIDE SURFACES.
- MATING COMPONENTS OR EQUIVALENT: CONNECTOR 12047781.
- TERMINALS MUST WITHSTAND A MINIMUM PUSHOUT FORCE OF 89 N (20 LBS).
- RECOMMENDED BODY MATERIAL: NYLON 66 OR EQUIVALENT FLEXIBLE THERMOPLASTIC.

MATING CONNECTOR INFORMATION

RECOMMENDED MATERIAL: P-1546 (CA-210) BRASS  
EXTRA SPRING TEMPER - TIN PLATED.  
PLATING THICKNESS: 0.003 - 0.005 MM  
TENSILE STRENGTH: 430 MPA  
NOTE - USE OF MATERIAL WITH A CONDUCTIVITY 20% IACS AT 68° F SHOULD BE APPROVED BY PACKARD ELECTRIC









SCALE 10:1

MATING TERMINAL INFORMATION

12065422	02	1	AB	POLYAMIDE COMPOUND CREAM	0.781
12047781	A4			POLYAMIDE COMPOUND BLACK	0.781
PART NO	REV/N/P	STATUS	MATERIAL SPECIFICATION AND COLOR	VOL CM <sup>3</sup>	

SYMBOL DEFINITION		MISSING SYMBOLS		REVISION HISTORY		AUTH	DR	APP'D
A DIMENSION WITHOUT AN INSPECTION REPORT SYMBOL ( ) DOES NOT REQUIRE INSPECTION. IT MAY BE CONTROLLED ON THE INDIVIDUAL COMPONENT DRAWING.	TOTAL NO OF INSPECTIONS REQUIRED	NO MISSING SYMBOLS	DATE	ISO	REV	DESCRIPTION		
	10	NO MISSING SYMBOLS NUMBER						
	10							



NOTES

- UNLESS OTHERWISE SPECIFIED AND/OR INDICATED: DIMENSIONS ARE TO FACE OF VIEW SHOWN AND AUTOMATICALLY ROUNDED BY COMPUTER FOR INSPECTION (SEE MATH MODEL FOR PRECISE DIMENSIONS). FOR ALL OTHER DIMENSIONS NOT SHOWN BUT REQUIRED FOR TOOL BUILD, SEE MATH MODEL FOR PRECISE TOOL PATH DATA.
- MATERIAL RECYCLING CODE PER ISO 11469, 111X10.11 CHARACTERS AS SHOWN TO BE LOCATED ON ANY EXTERIOR SURFACE. OPTIONAL CONSTRUCTION TO BE NO MATERIAL RECYCLING CODE.
- THIS PRODUCT IS NOT CATEGORIZED AS AN APPEARANCE ITEM. MINOR IMPERFECTIONS INCLUDING, BUT NOT LIMITED TO: FLOW MARKS, COLOR BLEMISHES, GATE VESTIGE, AND SOFT FLASH THAT DO NOT AFFECT THE FIT, FORM, OR FUNCTION OF THE PART ARE PERMISSIBLE PER DPNP-4.7-CS-01.
- THIS PART IS NOT CONTROLLED FOR AUTOMATIC FEEDING.
- THIS CONNECTOR WILL PASS THRU A Ø13 MIN HOLE.
- 111X10.11 DELPHI CORPORATE BRAND TO BE LOCATED ON ANY EXTERIOR SURFACE, PREFERABLY VISIBLE AT FINAL ASSEMBLY. OPTIONAL CONSTRUCTION FOR EXISTING TOOLING MAY BE "PED".
- FOR APPLICATION DATA SEE THE INDIVIDUAL APPLICATION DRAWINGS.



DRAWING TITLE		PART DRAWING	
DATE	DATE	DATE	DATE
BY	BY	BY	BY
APPROVED	APPROVED	APPROVED	APPROVED
CHECKED	CHECKED	CHECKED	CHECKED
DESIGNED	DESIGNED	DESIGNED	DESIGNED
SUBSTITUTES OF CONSTRUCTION AND REVISIONS		SUBSTITUTES OF CONSTRUCTION AND REVISIONS	
REVISIONS		REVISIONS	
TAXI CONN F M/P 150		TAXI CONN F M/P 150	
DRAWING NUMBER		DRAWING NUMBER	
12065180		12065180	
SHEET NO		SHEET NO	
511		511	
OF 1		OF 1	
R 129		R 129	

(4)	PROCESS SENSITIVE DIMENSION	THIRD ANGLE PROJECTION	DO NOT SCALE
	DIMENSIONS UNLESS INDICATED ARE IN MILLIMETERS		
	UNLESS OTHERWISE SPECIFIED		
	UNLESS OTHERWISE SPECIFIED		