

● THESE DIMENSIONS ARE CRITICAL TO THE MECHANICAL AND ELECTRICAL PERFORMANCE OF THE CONNECTION SYSTEM.

MATERIAL SPECIFICATIONS

RECOMMENDED

BASE METAL - CDA-210, EXTRA SPRING TEMPER

- TIN PLATING (WHERE APPLICABLE TO 125°C MAX CONTINUOUS USAGE): 0.0050±0.0025 MM (200±100 µIN) ELECTROPLATED TIN.
- USAGE OF PLATING TYPES OTHER THAN RECOMMENDED MUST BE APPROVED BY DELPHI PACKARD ELECTRIC SYSTEMS ENGINEERING.

MINIMUMS

ELECTRICAL CONDUCTIVITY - >28% IACS AT 20 °C. USE OF A MATERIAL WITH CONDUCTIVITY <28% IACS MUST BE APPROVED BY PACKARD ELECTRIC MATERIALS ENGINEERING.

TENSILE STRENGTH - 430 - 480 MPa

UNDERPLATING FOR TIN PLATING - FOR BASE MATERIALS CONTAINING 10% OR MORE ZINC, AN UNDERPLATE OF COPPER 0.0025 MM (100 µIN) MINIMUM THICK IS REQUIRED.

PROCESSING LUBRICANT - ANY PROCESSING LUBRICANT REMAINING ON TERMINALS MUST NOT ADVERSELY OCCASION ELECTRICAL PERFORMANCE FAILURE UNDER CONDITIONS OF MAXIMUM TEMPERATURE AND HUMIDITY. ALL LUBRICANTS MUST BE APPROVED BY DELPHI PACKARD ELECTRIC SYSTEMS ENGINEERING.

MATING BLADE INFORMATION





TYPE 102
SAME AS TYPE 101
EXCEPT AS SHOWN





TYPE 101



SYMBOL DEFINITION		MISSING SYMBOLS
A DIMENSION WITHOUT AN INSPECTION REPORT SYMBOL (--) DOES NOT REQUIRE INSPECTION. IT MAY BE CONTROLLED ON THE INDIVIDUAL COMPONENT DRAWING.	TOTAL NO OF INSPECTIONS REQUIRED: 14	NO MISSING SYMBOL NUMBER
	LAST NO. USED: 10	

KEY PRODUCT CHARACTERISTICS		
SAFETY/COMPLIANCE	FIT/FUNCTION	TOTAL ON DRAWING: 3
S/C CHECKPOINTS	F/F CHECKPOINTS	LAST NO. USED: 3

NO	TYPE	DESCRIPTION	RATIONALE	PTS	ZONE

ENG STATUS					ZONE	REVISION HISTORY	MFR	QP	APPROVED	
DATE	STR	REL	SVP	DOC						
13FEB08	R	08	-	-	-	CLEARED REVISION COLUMN), ALL PARTS - RESPANS TO PD	ZSNOOC	PBW	PBL	BM
05JAN07	R	09	-	-	-	ALL PARTS - REVISED SEALING CODE NOTE, ADDED TYPE COLUMN TO CHART, ADDED TYPE SYMBOLS FROM METHOD 2003 15JUN04A - ADDED TYPE 102 TOP VIEW	4816GB	MAC	MAC	BDB
02NOV01	R	10	-	-	-	ALL PARTS - UPDATED PDM ATTRIBUTES	482483	MAC	MAC	DLS
13APR12	R	11	-	-	-	12JUN09 - ADDED ADHESIVE NOTE AND INSPECTION SYMBOL TO PLUG!	42173B	MP	JWL	JPI





MATING CONNECTOR INFORMATION

NOTES

1. UNLESS OTHERWISE SPECIFIED AND/OR INDICATED:
   DIMENSIONS ARE TO FACE OF VIEW SHOWN AND AUTOMATICALLY ROUNDED BY COMPUTER FOR INSPECTION (SEE MATH MODEL FOR PRECISE DIMENSIONS). FOR ALL OTHER DIMENSIONS NOT SHOWN BUT REQUIRED FOR TOOL BUILD, SEE MATH MODEL FOR PRECISE TOOL PATH DATA. ALL RADII 0.4
2. RECOMMENDED MATERIAL - GLASS FILLED NYLON OR POLYESTER
3. WHEN USING THIS INFORMATION FOR A NEW DESIGN, REQUEST THE LATEST COPY OF THIS PRINT FROM PACKARD ELECTRIC

NOTES

1. UNLESS OTHERWISE SPECIFIED AND/OR INDICATED:
   DIMENSIONS ARE TO FACE OF VIEW SHOWN AND AUTOMATICALLY ROUNDED BY COMPUTER FOR INSPECTION (SEE MATH MODEL FOR PRECISE DIMENSIONS). FOR ALL OTHER DIMENSIONS NOT SHOWN BUT REQUIRED FOR TOOL BUILD, SEE MATH MODEL FOR PRECISE TOOL PATH DATA.
2. WHEN PARTS ARE SHIPPED THEY MUST BE PACKED IN PLASTIC BAGS OR SHIPPING CONTAINERS MUST BE LINED WITH PLASTIC LINERS. BAGS OR LINERS MUST BE SEALED TO AVOID FOREIGN MATTER.
3. SEALING CODE J - DESIGN WILL PASS SALT FOG AND IMMERSION TESTS WHEN CONSTRUCTION IS AS SPECIFIED IN ESA-710 (METRI-PACK) WHEN MATED TO MATING PART OR EQUIVALENT
4. FOR APPLICATION DATA SEE THE INDIVIDUAL APPLICATION DRAWINGS.
5. THIS PRODUCT IS NOT CATEGORIZED AS AN APPEARANCE ITEM. MINOR IMPERFECTIONS SUCH AS SCRATCHES, DIRT, DISCOLORATION, MARKS OR FINGERPRINTS, AS IS ACCEPTABLE, END SOFT FLASH THAT DO NOT AFFECT THE FIT, FORM, OR FUNCTION OF THE PART ARE PERMISSIBLE PER NAP 4.10-18.
6. FOR PART NUMBER WITH ADHESIVE, USE M3510001 OR ADHESIVE APPROVED BY MATERIALS ENGINEERING TO GLUE CONNECTOR SEAL TO CONNECTOR.

		15324076	A3	102	2	NONE	12052635	15305187	BLACK
		12129024	A3	101	2	NONE	12052635	12129025	BLACK
		12089501	B3	101	1	R	12089500	12103067	BROWN
	12186685	12052641	C4	101	2	NONE	12052635	12103067	BLACK
PART NO WITH ADHESIVE	REV	PART NO WITHOUT ADHESIVE	REV	TYPE	NUMBER OF CAVITIES	CAVITIES BLOCKED	CONNECTOR BODY	CONNECTOR SEAL	CONNECTOR COLOR

| | | | | | | | |