

MATERIAL SPECIFICATIONS

RECOMMENDED

BASE METAL - CDA-210, EXTRA SPRING TEMPER

PLATING - 0.00540.0025 MM THICK TIN

MINIMUMS

ELECTRICAL CONDUCTIVITY - ±20% IACS AT 20°C. USE OF A MATERIAL WITH CONDUCTIVITY < 20% IACS MUST BE APPROVED BY PACKARD ELECTRIC MATERIALS ENGINEERING.

TENSILE STRENGTH - 407 MPa

PLATING - FOR LOW ENERGY (±5v) AND NON-PASSENGER COMPARTMENT POWER CIRCUITS, 0.00540.0025 MM THICK TIN, FOR MATERIALS CONTAINING 10% OR MORE ZINC, AN UNDERPLATE OF COPPER 0.00540.0025 MM THICK IS REQUIRED.

MATING BLADE INFORMATION

SCALE 8:1



SECTION A-A



SECTION B-B



OPTIONAL CONSTRUCTION



SECTION C-C

OPTIONAL CONSTRUCTION

NOTES:

1. UNLESS OTHERWISE SPECIFIED AND/OR INDICATED:
   DIMENSIONS ARE TO FACE OF VIEW SHOWN AND AUTOMATICALLY ROUNDED BY COMPUTER FOR INSPECTION.
   (SEE MATH MODEL FOR PRECISE DIMENSION)
   ALL OTHER DIMENSIONS AND TOLERANCES ONLY REQUIRED FOR TOOL BUILD, SEE MATH MODEL FOR PRECISE TOOL PATH DATA.
   ALL RADII 0.40
   DRAFT IS 1° ON ALL OUTSIDE SURFACES
2. RECOMMENDED MATERIAL: GLASS REINFORCED NYLON OR POLYESTER

MATING CONNECTOR INFORMATION

SYMBOL DEFINITION		MISSING SYMBOLS
A DIMENSION WITHOUT AN INSPECTION REPORT SYMBOL (__) DOES NOT REQUIRE INSPECTION, IT MAY BE CONTROLLED ON THE INDIVIDUAL COMPONENT DRAWING.	TOTAL NO OF INSPECTIONS REQUIRED	15
	LAST NO. USED	15

NO MISSING SYMBOL NUMBER

DWG STATUS						REVISION HISTORY			
DATE	STS	REL	N/P	DIR	ZONE		WIN	BY	APVD
1JUN94	R	001	-	-	-	CLEARED REV COLUMN(15JUN94) - RELEASED	9930051	KEB	MJT JP
13OCT95	R	002	-	-	-	15394008 - RELEASED	9930051	KEB	JP
8JAN96	R	003	-	-	-	15459771 - RELEASED	2340388	KEB	RDH JP
12APR96	R	004	-	-	-	ADDED OPTIONAL CONSTRUCTION	2389511	CJC	JP
18APR97	R	005	-	-	-	15459771 - CABLE SEAL WAS 15394867 - 95% LT.	2511033	LEE	KEB JP
11APR01	R	006	-	-	-	12188695 & 12188829 - OBSOLETE	2380416	RDH	RDH JP
13DEC01	R	007	-	-	-	CORRECTED P/N 12162188 REVISION LEVEL FROM C TO B1	2472711	MB	MB BO
8JAN14	R	008	-	-	-	ALL ACTIVE PARTS - ADDED LUBEWELL LUBRICANT NOTE	4249968	JAS	JAN KBA
21FEB17	R	009	-	-	-	15324384-B5 - UPDATED PART AVAILABILITY	4357618	JTL	JTL KC

NOTES:

1. UNLESS OTHERWISE SPECIFIED AND/OR INDICATED:
   DIMENSIONS ARE TO FACE OF VIEW SHOWN AND AUTOMATICALLY ROUNDED BY COMPUTER FOR INSPECTION.
   (SEE MATH MODEL FOR PRECISE DIMENSION)
   ALL OTHER DIMENSIONS AND TOLERANCES ONLY REQUIRED FOR TOOL BUILD, SEE MATH MODEL FOR PRECISE TOOL PATH DATA.
2. WHEN PARTS ARE SHIPPED, THEY MUST BE PACKED IN PLASTIC BAGS OR SHIPPING CONTAINERS MUST BE LINED WITH PLASTIC LINERS. BAGS OR LINERS MUST BE SEALED TO AVOID ENTRY OF FOREIGN MATTER
3. FOR LEAD LENGTH CALCULATIONS, DISTANCE FROM MATING END OF CONNECTOR TO FRONT OF CABLE CORE IS 10.15/7.05
4. SEALING CODE 3

   DESIGN WILL PASS SALT FOG AND IMMERSION TEST AFTER CONDITIONING AS SPECIFIED IN ESA-664 (WEATHER-PACK), ESA-710 (METRI-PACK), ESA-650 (UNDERHOOD MICRO-PACK), C-4006 (MICRO-PACK CONNECTOR), ETC. - WHEN MATED TO MATING PART OR EQUIVALENT
5. FOR PARTS NUMBERS WITH ADHESIVE, USE PM003510 OR ADHESIVE APPROVED BY MATERIALS ENGINEERING TO GLUE CONNECTOR SEAL TO CONNECTOR
6. S-60-T LUBEWELL LUBRICANT CAN BE USED AS AN AUXILIARY SUPPORT ON THE CABLE INSTALLATION PROCESS.
7. FOR APPLICATION DATA SEE THE INDIVIDUAL APPLICATION DRAWINGS.





TYPE 105

SAME AS TYPE 101 EXCEPT AS SHOWN



TYPE 102

SAME AS TYPE 101 EXCEPT AS SHOWN



TYPE 103

SAME AS TYPE 101 EXCEPT AS SHOWN







TYPE 101



TYPE 104

SAME AS TYPE 101 EXCEPT AS SHOWN

		15405971	02	AA	105	B	12162187	12040756	15422575 - PURPLE
		15394888	01	AA	104	C	12162187	12040756	15394067 - GRA LT.
		15324665	01	AA	101	NONE	15324666	12040757	12040757 - GREEN
		15324385	A2	-	103	A, C	12162187	12040756	15324383 - DK. RED
		15324384	A2	-	102	B, D	12162187	12040756	15324383 - DK. RED
12188695	B2	12188829	A2	-	101	NONE	12162187	12188823	12110186 - ORANGE
		12188395	A1	-	103	A, C	12188391	12040756	12188396 - PURPLE
		12188394	A1	-	102	B, D	12162187	12040756	12188396 - PURPLE
		12162191	B1	-	101	NONE	12162187	12040756	12124886 - BLUE
		12162190	B1	-	101	NONE	12162187	12040756	12110186 - ORANGE
		12162189	B1	-	101	NONE	12162187	12040756	12079081 - TAN
		12162188	B2	-	101	NONE	12162187	12040757	12040757 - GREEN
P/N WITH ADHESIVE	REV	N/P	TYPE	P/N WITHOUT ADHESIVE		BLOCKED CAVITIES	CONNECTOR	CONNECTOR SEAL	CABLE SEAL & COLOR

DELPHI

DELPHI CORPORATION

COPYRIGHT 1994 DELPHI AUTOMOTIVE SYSTEMS LLC

THIS DRAWING IS THE PROPERTY OF DELPHI CORPORATION AND IS LOANED SUBJECT TO THE AGREEMENT OR UNDERSTANDING THAT IT WILL NOT BE REPRODUCED, COPIED OR LOANED IN WHOLE OR IN PART OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR A PART THEREOF EXCEPT UNDER WRITTEN PERMISSION AND AGREEMENT.

PART DRAWING

ENGINEERING RELEASE

APVD	BRIAN R. DEB	02FEB94
APVD	BRIAN R. DEB	02FEB94
APVD	M. A. TURNER	08FEB94
APVD		
APVD		

SUBSTITUTED IF BROKEN AND RECYCLED CONTENT PER DELPHI-1 (APPROVED)

SIZE	DWG
B	

DRAWING NAME

TAXI MSM CONN F M/P 150.2 SLD

DRAWING NUMBER

12162268

SIZE	WHOLE	FRAME NO	SHEET NO	REV
A3=2	411	12 OF 21	1 OF 1	B (ECN)

| | | | | | | | | |