



YAZAKI PART NO.	K	L	M	APPLICABLE WIRE SIZE	TREATMENT
7116-1530. \square	3.30	5.50	7.70	AVS0.3~0.85	TIN PLATING
7116-1530-08. \square				CAVUS0.5 \triangle	EQUIVALENT
7116-1531	3.60	6.00	8.70	AVS1.25~2.00	TIN PLATING
7116-1531-08				EQUIVALENT	GOLD PLATING

注 記
 1. 材質
 本体 : 黄銅 t=0.25
 パネ : ベリリウム銅 t=0.20

NOTES
 1. MATERIAL
 BODY : BRASS, t=0.25
 SPRING : COPPER BERYLLIUM, t=0.20

LET	DATE	REVISION RECORD	NO.	CHKD	VENDOR	MATL. SPEC.	TREAT. & FIN.	
\triangle	97.07.30	ADDED WIRE SIZE	C97-7658	K. U		SEE NOTES		
\triangle	97.06.24	CHANGED FORM. \square	C97-M294	H. K	CUSTOMER			
\triangle	89.04.21	形状変更	C89-6612	矢 部	CUSTOMER PART NO.			
\triangle	89.01.09	形状変更	C89-6068	T. N	CUSTOMER DWG NO.			
	88.09.27	NEW	8MC-1230	S. K	OFFICE			
					TRIAL PART NO.			
GENERAL TOLERANCE					NAME \triangle E TYPE TERMINAL			
	10MAX	50MAX	100MAX	250MAX	2500VR	PART NO. 7116-1530 ETC.		
A	± 0.15	± 0.2	± 0.3	± 0.5	± 0.75	CH. CODE		
B	± 0.2	± 0.3	± 0.55	± 0.95	± 1.4	DWG NO. 7116-1530:R		
C	± 0.3	± 0.5	± 0.8	± 1.4	± 2	SET DWG NO.		
SPECIFIED					MASS	YAZAKI CORPORATION		
					g	97.08.26 778.24 97.08.20 720 88.09.27 97.07.01		