


| PART NUMBER    | MATERIAL        | COLOUR             | WIRE O. D.     |
|----------------|-----------------|--------------------|----------------|
| 7158-3030-50   | SILICONE RUBBER | RED<br>(RAL 2002)  | 1.2 ~ 1.7 mm   |
| △ 7158-3031-90 | SILICONE RUBBER | BLUE<br>(RAL 5012) | 1.63 ~ 2.2 mm  |
| △ 7158-3033-40 | SILICONE RUBBER | LIGHT GREY         | 2.20 ~ 2.69 mm |

NOTES:  
 1. APPLICABLE TERMINALS: 7114-4102-02 etc.  
 7116-4102-02 etc.  
 2. APPLICABLE FOR CAVITY DIAMETER 4.80 mm.  
 3. RUBBER PARTS GENERAL TOLERANCE ±0.2 mm.



| LET   | DATE     | REVISION RECORD  | NO.      | CHKD   | VENDOR NO.        | DWG TYPE     | DWG SOURCE | DWG DATE  | UNIT | SCL  | ANGLE | PART NO.          | CH. CODE | DWG NO.          | SET DRW NO. |  |  |  |  |       |       |        |        |        |       |   |       |      |      |      |       |      |   |      |      |       |       |      |      |   |      |      |      |      |    |      |   |  |                         |  |
|---|----------|------------------|----------|--------|-------------------|--------------|------------|-----------|------|------|-------|-------------------|----------|------------------|-------------|--|--|--|--|-------|-------|--------|--------|--------|-------|---|-------|------|------|------|-------|------|---|------|------|-------|-------|------|------|---|------|------|------|------|----|------|---|--|-------------------------|--|
| △   | 09/02/27 | CHANGED PART NO. | Y09-0054 | V.M.   | CUSTOMER          | R            | NEW        | 14.7.2008 | mm   | 10/1 | 3     | 7158-3030-50 ETC. |          | 7158-3030-50 : R |             |  |  |  |  |       |       |        |        |        |       |   |       |      |      |      |       |      |   |      |      |       |       |      |      |   |      |      |      |      |    |      |   |  |                         |  |
| △   | 08/07/11 | CHANGED SHAPE    | Y08-0033 | V.M.   | CUSTOMER PART NO. | APPROVED     | CHECKED    |           |      |      |       |                   |          |                  |             |  |  |  |  |       |       |        |        |        |       |   |       |      |      |      |       |      |   |      |      |       |       |      |      |   |      |      |      |      |    |      |   |  |                         |  |
| △   | 02/04/10 | ADD PART NO.     | C02-E094 | M.L.   | CUSTOMER DWG NO.  | T. SCHALLER  | V. MAHOVIC |           |      |      |       |                   |          |                  |             |  |  |  |  |       |       |        |        |        |       |   |       |      |      |      |       |      |   |      |      |       |       |      |      |   |      |      |      |      |    |      |   |  |                         |  |
|   | 99/02/23 | NEW              | C99-E013 | G.N.   | OFFICE YKE        | P.P. Malonic |            |           |      |      |       |                   |          |                  |             |  |  |  |  |       |       |        |        |        |       |   |       |      |      |      |       |      |   |      |      |       |       |      |      |   |      |      |      |      |    |      |   |  |                         |  |
| <table border="1"> <thead> <tr> <th colspan="7">GENERAL TOLERANCE</th> </tr> <tr> <th></th> <th>10MAX</th> <th>50MAX</th> <th>100MAX</th> <th>250MAX</th> <th>250OVR</th> <th>ANGLE</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>±0.15</td> <td>±0.2</td> <td>±0.3</td> <td>±0.5</td> <td>±0.75</td> <td>±30'</td> </tr> <tr> <td>B</td> <td>±0.2</td> <td>±0.3</td> <td>±0.55</td> <td>±0.95</td> <td>±1.4</td> <td>±30'</td> </tr> <tr> <td>Ⓢ</td> <td>±0.3</td> <td>±0.5</td> <td>±0.8</td> <td>±1.4</td> <td>±2</td> <td>±30'</td> </tr> </tbody> </table> |          |                  |          |        |                   |              |            |           |      |      |       | GENERAL TOLERANCE |          |                  |             |  |  |  |  | 10MAX | 50MAX | 100MAX | 250MAX | 250OVR | ANGLE | A | ±0.15 | ±0.2 | ±0.3 | ±0.5 | ±0.75 | ±30' | B | ±0.2 | ±0.3 | ±0.55 | ±0.95 | ±1.4 | ±30' | Ⓢ | ±0.3 | ±0.5 | ±0.8 | ±1.4 | ±2 | ±30' | NAME 1.5 SEALED SYSTEM CONNECTOR<br>WIRE SEAL |  | TREAT. & FIN. SEE NOTES |  |
| GENERAL TOLERANCE   |          |                  |          |        |                   |              |            |           |      |      |       |                   |          |                  |             |  |  |  |  |       |       |        |        |        |       |   |       |      |      |      |       |      |   |      |      |       |       |      |      |   |      |      |      |      |    |      |   |  |                         |  |
|   | 10MAX    | 50MAX            | 100MAX   | 250MAX | 250OVR            | ANGLE        |            |           |      |      |       |                   |          |                  |             |  |  |  |  |       |       |        |        |        |       |   |       |      |      |      |       |      |   |      |      |       |       |      |      |   |      |      |      |      |    |      |   |  |                         |  |
| A   | ±0.15    | ±0.2             | ±0.3     | ±0.5   | ±0.75             | ±30'         |            |           |      |      |       |                   |          |                  |             |  |  |  |  |       |       |        |        |        |       |   |       |      |      |      |       |      |   |      |      |       |       |      |      |   |      |      |      |      |    |      |   |  |                         |  |
| B   | ±0.2     | ±0.3             | ±0.55    | ±0.95  | ±1.4              | ±30'         |            |           |      |      |       |                   |          |                  |             |  |  |  |  |       |       |        |        |        |       |   |       |      |      |      |       |      |   |      |      |       |       |      |      |   |      |      |      |      |    |      |   |  |                         |  |
| Ⓢ   | ±0.3     | ±0.5             | ±0.8     | ±1.4   | ±2                | ±30'         |            |           |      |      |       |                   |          |                  |             |  |  |  |  |       |       |        |        |        |       |   |       |      |      |      |       |      |   |      |      |       |       |      |      |   |      |      |      |      |    |      |   |  |                         |  |
| YAZAKI CORPORATION  |          |                  |          |        |                   |              |            |           |      |      |       |                   |          |                  |             |  |  |  |  |       |       |        |        |        |       |   |       |      |      |      |       |      |   |      |      |       |       |      |      |   |      |      |      |      |    |      |   |  |                         |  |

1 2 3