



5			
SUB-ASSEMBLY PART NUMBER	NO.	PART NUMBER	
7282-2432-30	1	7182-2432-30	
1202-2432-30		7450 0470	Γ

(∅ 39.15)						


RECOMMENDED PASS-THROUGH HOLE DIMENSION (1mm CLEARANCE ALL AROUND) (1/1)




FRONT ISOMETRIC VIEW RE



REAR ISOMETRIC VIEW (1/1)





												CUSTOMER				
												CUSTOMER PA		CUSTOMER		
												OFFICE	YNA		TRIAL PA	\ RT
												VENDOR				
					GENERA	L TOLERAN	NCE	_		_		VENDOR NO.				
	10MAX	50MAX	100MAX	250MAX	2500VR	R5 MAX	R10 MAX	R20 MAX	R20 OVR	ANGLE	ECCENT	DWG TYPE	DWG SOURCE	. [[DWG DATE	Ξ
Α	±0.15	±0.20	±0.30	±0.50	±0.75					±3°	0.1	R	7282-2432-30:M	<u>م</u>	12-07-2017	7
В	±0.20	±0.30	±0.55	±0.95	±1.40	±0.20	±0.30	±0.50	±2.50	±3°	0.1	APPROVED	CHECKED	CH	ECKED	
\bigcirc	±0.30	±0.50	±0.80	±1.40	±2.00					±3°	0.15					
SPE	CIFIED									MASS						
											(13.00) <i>g</i>					05
				4						5						