

△ SEC. A-A




TABLE 1

SUB ASSEMBLY PART NO. AND CH. CODE	NO.	PART NO. AND CH. CODE	MATERIAL	COLOR	QTY.
7283-7023-10 ETC.	①	SEE TABLE 2	PBT	SEE TABLE 2	1
	②	7157-4103	PBT	NATURAL	1
	③	7137-2211-80	SILICONE RUBBER	RED IRON	1

TABLE 2

SUB ASSEMBLY PART NO. AND CH. CODE	PART NO. AND CH. CODE	COLOR
△ 7283-7023	7183-7023	NATURAL
7283-7023-10	7183-7023-10	DARK GRAY
△ 7283-7023-30	7183-7023-30	BLACK
△ 7283-7023-40	7183-7023-40	LIGHT GRAY
△ 7283-7023-50	7183-7023-50	ORANGE
△ 7283-7023-60	7183-7023-60	GREEN
△ 7283-7023-80	7183-7023-80	BROWN
△ 7283-7023-90	7183-7023-90	BLUE

NOTES

- 1. APPLICABLE TERMINAL NO. : 7116-4025 ETC.
- 2. MATING PART NO. : 7282-7023-10 ETC.
- △ 3. APPLICABLE RUBBER STOPPER NO. : 7158-3006-90 ETC.

注記

- 1. 適用端子番 : 7116-4025 ETC.
- 2. 嵌合相手番 : 7282-7023-10 ETC.
- △ 3. 適用ゴム栓番 : 7158-3006-90 ETC.

△	2008.05.16	CHANGED FORM ETC.	C08-Z358	S. S
△	03.08.27	CHANGED NAME & CORRECTION OF A CLERICAL ERROR	C03-X519	E. F
△	97.07.25	ADDED PART NO.	C97-M505	M. T
△	89.10.04	ADDED PART NO.	C89-M068	M. H
△	89.08.19	CHANGED FORM & RENEW	C89-L866	M. T
△	89.02.22	NEW	C89-L380	T. M
LET	DATE	REVISION RECORD	NO.	CHKD

GENERAL TOLERANCE					
	10MAX	50MAX	100MAX	250MAX	2500VR
A	±0.15	±0.2	±0.3	±0.5	±0.75
B	±0.2	±0.3	±0.55	±0.95	±1.4
◎	±0.3	±0.5	±0.8	±1.4	±2
SPECIFIED					MASS

CUSTOMER	CUSTOMER PART NO.	CUSTOMER DWG NO.
OFFICE	TRIAL PART NO.	
VENDOR	VENDOR NO.	
DWG TYPE	DWG SOURCE	DWG DATE
R	NEW	88.07.27
APPROVED	CHECKED	CHECKED
小栗	鈴木	
08.05.23	08.05.22	
UNIT	SCL	ANGLE
mm	3/2/1	3
DESIGN	DRAWN	
M. TSUJI	J. GALLARES	

MATL. SPEC.	SEE TABLE 1	TREAT. & FIN.
NAME 2.3II 2P SEALED CONNECTOR		
△ HOUSING FEMALE SUB ASSEMBLY		
PART NO. CH. CODE	△ 7283-7023-10 ETC.	
DWG NO.	7283-7023-10:R	SET DWG NO.
YAZAKI CORPORATION		