



SEC. A-A

SUB ASSEMBLY PART NO. AND CH. CODE	NO.	PART NO. AND CH. CODE	MATERIAL	COLOR	QTY.
7283-8456-30, C	①	7183-8456-30	PBT-G	BLACK	1
	②	7137-2942-80	SILICONE RUBBER	RED-IRON	1
	③	7158-6079	PBT-G	NATURAL	1

注記

- かん合相手品番 : XF2T-14A464-YC (補機直結)
- 適用端子品番 : 7116-4102-02 (CAVS 0.3~0.5)
: 7116-4103-02 (CAVS 0.85~1.25)
- 適用ゴム栓品番 : 7158-3003-90 (CAVS 0.3~0.5)
: 7158-3004-40 (CAVS 0.85~1.25)

NOTES

- MATING PART NO. : XF2T-14A464-YC (DIRECT CONNECTOR EQUIPMENT)
- APPLICABLE TERMINAL NO. : 7116-4102-02 (CAVS 0.3~0.5)
: 7116-4103-02 (CAVS 0.85~1.25)
- APPLICABLE RUBBER STOPPER NO. : 7158-3003-90 (CAVS 0.3~0.5)
: 7158-3004-40 (CAVS 0.85~1.25)

GENERAL TOLERANCE											
	10 MAX	50 MAX	100 MAX	250 MAX	250 OVR	R5 MAX	R10 MAX	R20 MAX	R20 OVR	ANGLE	ECCENT
A	±0.15	±0.2	±0.3	±0.5	±0.75	±0.2	±0.3	±0.5	±2.5	±3°	0.1
B	±0.2	±0.3	±0.55	±0.95	±1.4					±3°	0.1
C	±0.3	±0.5	±0.8	±1.4	±2					±3°	0.15

LET	DATE	REVISION RECORD	NO.	CHKD	CUSTOMER	CUSTOMER PART NO.	CUSTOMER DWG NO.	MATL. SPEC.	TREAT. & FIN.						
③	10/10/15	CHANGED PART NAME	C10-ZA72	N. B	CUSTOMER			SEE TABLE							
②	08/09/29	CHANGED FORM, C	C08-Z705	M. M											
①	03/11/03	CHANGED FORM, A	C03-X554	M. M											
	02/11/12	NEW	C02-Y300	E. N	OFFICE		TRIAL PART NO.								
GENERAL TOLERANCE					VENDOR NO.					NAME ③ 060 2P SEALED					
GENERAL TOLERANCE					VENDOR NO.					HOUSING FEMALE SUB ASSEMBLY					
	10MAX	50MAX	100MAX	250MAX	250OVR	ANGLE	ECCENT	DWG TYPE	DWG SOURCE	DWG DATE	UNIT	SCL	ANGLE	PART NO. CH. CODE	
A	±0.15	±0.2	±0.3	±0.5	±0.75	±30°	0.1	R	NEW	02/11/12	mm	2:1	3	7283-8456-30, C	
B	±0.2	±0.3	±0.55	±0.95	±1.4	±30°	0.1	APPROVED	CHECKED	CHECKED	DESIGN	DRAWN	DWG NO.	7283-8456-30:R	
C	±0.3	±0.5	±0.8	±1.4	±2	±30°	0.15	S. MIZUSE		R. CABANGAL	E. NAGANO	N. BUSTARGA		SET DWG NO.	
SPECIFIED					MASS						YAZAKI CORPORATION				
					g	10/10/15					10/10/15				

1

2

3