



SUB ASSEMBLY PART NO. AND CH. CODE		NO.	PART NO. AND CH. CODE	△ PART NAME	MATERIAL	COLOR	QTY.
△ 7283-8852-30, [D]	①	7183-8852-30	△ RH TYPE 3P HOUSING FEMALE (CODE A)	PBT	BLACK	1	
	②	7158-5264	△ RH TYPE 3P FRONT HOLDER FEMALE	PBT	△ 3 NATURAL	1	
	③	7137-2814-80	△ RH TYPE 3P PACKING	SILICONE RUBBER	BROWN	1	
△ 7287-0178-40	④	7187-0178-40	△ RH TYPE 3P HOUSING FEMALE (CODE B)	PBT	LIGHT GRAY	1	
	②	7158-5264	△ RH TYPE 3P FRONT HOLDER FEMALE	PBT	NATURAL	1	
	③	7137-2814-80	△ RH TYPE 3P PACKING	SILICONE RUBBER	BROWN	1	

注記

- △ 1. かん合相手品番 : 7282-8852-30 (CODE A のみ)
- 2. 適用端子品番 : 7116-4415-02 ETC.
- 3. 適用コネクタ品番 : 7158-3165-90, 7158-3166-60, 7158-3167-80
7158-3168-80
- 4. 適用防水栓品番 : 7158-3169-40

NOTES

- △ 1. MATING PART NO. : 7282-8852-30 (CODE A ONLY)
- 2. APPLICABLE TERMINAL NO. : 7116-4415-02 ETC.
- 3. APPLICABLE SEAL RUBBER NO. : 7158-3165-90, 7158-3166-60, 7158-3167-80
7158-3168-80
- 4. APPLICABLE UNUSED CAVITY PLUG: 7158-3169-40

△	DATE	REVISION RECORD	NO.	CHKD
△ 6	2011/01/26	CHANGED PART NAME, ETC.	C11-Z051	Y. F
△ 5	2006/11/28	ADDED PART NO., ETC., [D]	C06-ZD06	Y. I
△ 4	05/01/07	CHANGED FORM, [C]	C04-ZF72	T. Y
△ 3	03/08/07	CHANGED CODE, [B]	C03-X324	T. Y
△ 2	02/05/17	CHANGED FORM, [A]	C02-X538	T. Y
△ 1	02/02/06	ELIMINATE SECTION	C02-X199	T. Y
	01/11/08	NEW	C01-Y135	T. Y

GENERAL TOLERANCE								
	10MAX	50MAX	100MAX	250MAX	2500VR	ANGLE	ECCENT	
A	±0.15	±0.2	±0.3	±0.5	±0.75	±30'	O.1	
B	±0.2	±0.3	±0.55	±0.95	±1.4	±30'	O.1	
(C)	±0.3	±0.5	±0.8	±1.4	±2	±30'	O.15	
SPECIFIED							MASS	

CUSTOMER		VENDOR	
CUSTOMER PART NO.	CUSTOMER DWG NO.	VENDOR NO.	TRIAL PART NO.
APPROVED	CHECKED	CHECKED	DESIGN
M. KASHIYAMA		Y. FUKASE	M. KASHIYAMA
2011/01/26		2011/01/26	01/05/08
			DRAWN
			R. EVANGELISTA
			2011/01/26

MATL. SPEC.	TREAT. & FIN.
SEE TABLE	
NAME △ RH TYPE 3P HOUSING	
FEMALE SUB ASSEMBLY	
PART NO. CH. CODE	△ 7283-8852-30 ETC.
DWG NO.	7283-8852-30:R
SET DWG NO.	
YAZAKI CORPORATION	