



2		3				
SUB ASSEMBLY PART NO. AND CH. CODE	NO.	PART NO. AND CH. CODE	△PART NAME	MATERIAL	COLOR	QTY.
7283-8853-30, [D]	①	7183-8853-30	HOUSING	PBT	BLACK	1
	②	7158-5266 △	FRONT HOLDER	PBT	△NATURAL	1
	③	7137-2815-80	PACKING	SILICONE RUBBER	BROWN	1

注記

1. 嵌合相手品番 : 7282-8853-30
2. 適用端子品番 : 7116-4415-02 ETC.
- △ 3. 適用「L」栓品番 : 7158-3165-90 ETC.
4. 適用防水栓品番 : 7158-3169-40

NOTES

1. MATING PART NO. : 7282-8853-30
2. APPLICABLE TERMINAL NO. : 7116-4415-02 ETC.
- △ 3. APPLICABLE RUBBER SEAL NO. : 7158-3165-90 ETC.
4. APPLICABLE UNUSED CAVITY PLUG: 7158-3169-40

△	DATE	REVISION RECORD	NO.	CHKD	VENDOR
△	06/12/19	CHANGED FORM, ETC. [D]	C06-ZD62	Y. I	
△	05/06/07	CHANGED FORM. [C]	C05-Z863	S. K	
△	03/08/07	CHANGED CODE. [B]	C03-X324	T. Y	CUSTOMER
△	02/05/17	CHANGED FORM. [A]	C02-X538	T. Y	CUSTOMER PART NO.
△	02/02/06	ELIMINATE SECTION	C02-X199	T. Y	CUSTOMER DWG NO.
△	01/11/08	NEW	C01-Y135	T. Y	OFFICE

GENERAL TOLERANCE										MATERIAL SPEC.		TREAT. & FIN.						
LET	DATE	10MAX	50MAX	100MAX	250MAX	2500VR	ANGLE	ECCENT	DWG TYPE	DWG SOURCE	DWG DATE	UNIT	SCL	ANGLE	PART NO. CH. CODE	NAME	TRIAL PART NO.	SET DWG NO.
A		±0.15	±0.2	±0.3	±0.5	±0.75	±30'	0.1	R	NEW	01/11/08	mm	2:1	3	7283-8853-30, [D]	RH TYPE CONNECTOR 4P		
B		±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.15	APPROVED	CHECKED					7283-8853-30:R	SUB ASSEMBLY FEMALE		
③		±0.3	±0.5	±0.8	±1.4	±2	±30'	0.15										
SPECIFIED										DESIGN	DRAWN			YAZAKI CORPORATION				
										M. KASHIYAMA	S. SANTOS							
										01/05/08	2006/12/19							

ISSUE MARK